

Steel Mechanical Edge-O-Dock Leveler 72 In. Ramp Width 20,000 Lb. Capacity Brown

MODEL FM-2072

Loading Dock Equipment / Edge-O-Dock Levelers

PRODUCT OVERVIEW

The Edge-O-Dock leveler permanently attaches to face of dock. It is recommended for docks to be at least forty-eight (48) inches high. When the trailer departs, the lip drops automatically behind the face of the bumpers. It comes complete with bumpers and installation instructions. Standard ramping is twenty-nine (29) inches. A steel dock edge, or approach ramp is required for proper installation. The mechanical Edge-O-Dock is operated by placing the actuation handle into the pocket of the inner lip and pulling down toward the floor. The operator then pushes the handle forward until the lip rests on the truck bed. As the trailer departs, the lip retracts behind the bumper face automatically.

KEY FEATURES

- Easy install allows unit to quickly mount to any loading dock with a steel dock edge
- Tread plate design offers a positive non-slip gripping action
- Concrete recess not required
- Solid steel construction offers long lasting reliable use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
510 lbs

ASSEMBLED SIZE
99" W x 15" L x 18" H

SHIP WEIGHT
523 lbs

PACKAGE 1 SIZE
72" W x 14" D x 22" H

COLOR / FINISH
Brown

FREIGHT TYPE
LTL Loose

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	20,000
Service Range Above Dock (in.)	5
Service Range Below Dock (in.)	5
Bumper Width (in.)	8
Bumper Length (in.)	2
Bumper Height (in.)	18
Ramp Width (in.)	72
Ramping Length (in.)	29
Bumper projection including rubber bumper (in.)	15

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=5>