

Steel Non Telescoping Lift Boom 24 In. Fork Pocket Center 8,000 Lb. Capacity Blue and Yellow

MODEL LM-1NT-8-24

Fork Truck Attachments / Lift Master Fork Truck Booms



PRODUCT OVERVIEW

The non-telescoping lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

CORE PRODUCT DATA

ASSEMBLED WEIGHT
476 lbs

ASSEMBLED SIZE
32" W x 80.125" L x 23.5" H

SHIP WEIGHT
476 lbs

PACKAGE 1 SIZE
32" W x 80" D x 24" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Loose

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	8,000
Fork Pocket Center (in.)	24
Fork Pocket Width/Height (in.)	7-1/4 x 2-1/4
Restraint Length (in.)	36
Boom Style	Non-Telescoping
Minimum/Maximum Hook Point (in.)	36/78
Single-Hook Capacity at 36" (lb.)	8000
Single-Hook Capacity at 48" (lb.)	6650
Single-Hook Capacity at 60" (lb.)	6000
Single-Hook Capacity at 72" (lb.)	5300
Single-Hook Capacity at 78" (lb.)	4850
Boom Type	Lift Master Boom
OSHA	1910.178(a)(4)
Overall Height (in.)	23-1/2
Overall Length (in.)	80-1/8
Overall Width (in.)	32
Vertical Center of Gravity (in.)	11-31/32
Horizontal Center of Gravity (in.)	30-3/8

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA