

# Steel Orbit Telescoping Lift Boom 36 In. Fork Pocket Center 8,000 Lb. Capacity Blue

**MODEL LM-OBT-8-36**

Fork Truck Attachments / Orbiting Fork Truck Booms

## PRODUCT OVERVIEW

The orbit lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a locking detent and safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
702 lbs

**ASSEMBLED SIZE**  
44" W x 85.25" L x 29" H

**SHIP WEIGHT**  
792 lbs

**PACKAGE 1 SIZE**  
44" W x 96" D x 35" H

**COLOR / FINISH**  
Blue (Base Frame)/Yellow  
(Extension)


**FREIGHT TYPE**  
LTL Loose

**AVAILABILITY** Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP:** --

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                     |               |
|-------------------------------------|---------------|
| Uniform Capacity (lb.)              | 8,000         |
| Fork Pocket Center (in.)            | 36            |
| Fork Pocket Width (in.)             | 7-1/4 x 2-1/4 |
| Restraint Length (in.)              | 36            |
| Boom Style                          | Telescoping   |
| Minimum/Maximum Hook Point (in.)    | 36/144        |
| Single-Hook Capacity at 36" (lb.)   | 8000          |
| Single-Hook Capacity at 48" (lb.)   | 6650          |
| Single-Hook Capacity at 60" (lb.)   | 6000          |
| Single-Hook Capacity at 72" (lb.)   | 5300          |
| Single-Hook Capacity at 84" (lb.)   | 4650          |
| Single-Hook Capacity at 96" (lbs.)  | 4000          |
| Single-Hook Capacity at 108" (lbs.) | 3500          |
| Single-Hook Capacity at 120" (lbs.) | 3000          |
| Single-Hook Capacity at 132" (lbs.) | 2600          |
| Single-Hook Capacity at 144" (lbs.) | 2200          |
| Overall Extended Height (in.)       | 96-1/8        |
| Retracted Hook Height (in.)         | 5-1/8         |
| Extended Hook Height (in.)          | 76-9/16       |
| Overall Extended Length (in.)       | 148-1/2       |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?PID=1775>