

Steel Traction Drive Cart Top Load with Gate 59 In. x 28 In. x 44 In. 750 Lb. Capacity Black

MODEL NE-CART-2

Industrial Carts & Dollies / Traction-Drive Carts

PRODUCT OVERVIEW

This traction-drive cart features built-in traction-drive system for easy transportability. Ideal for applications including mail rooms, hospitals, supermarkets, hotels and warehouses. Features electric drive motor with batteries for power. Internal battery charger is included. Variable throttle speed control for precise maneuvering and positioning is located in the handle. Speed control is conveniently located in handle. Handle pivots back towards operator and includes horn, automatic brake and emergency stop. Each shelf includes a non-slip tread plate surface. Includes on-board charger and battery level indicator.

KEY FEATURES

- Each shelf includes a non-slip tread plate surface
- Emergency safety stop belly-bump button switch provides added user safety
- Cart rolls smoothly on non-marking solid foam filled wheels
- Battery level indicator signals user when battery gets low

CORE PRODUCT DATA

ASSEMBLED WEIGHT
406 lbs

ASSEMBLED SIZE
28" W x 59" L x 44" H

SHIP WEIGHT
349 lbs

PACKAGE 1 SIZE
40" W x 64" D x 52" H

COLOR / FINISH
Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Overall Capacity (lb.)	750
Platform Length (in.)	46
Platform Width (in.)	24-3/4
Deck Height (in.)	14
Steering Wheel Diameter (in.)	9
Steering Wheel Width (in.)	3-1/4
Number of Steering Wheels	2
Steering Wheel Type	Solid Foam Tires
Drive Wheel Diameter (in.)	10
Drive Wheel Width (in.)	3-1/4
Number of Drive Wheels	2
Drive Wheel Type	Solid Foam Tires
Handle Height (in.)	44-11/16
Railing Height (in.)	12
Fast Travel Speed Loaded (miles per hour)	2.5
Fast Travel Speed Unloaded (miles per hour)	2.8
Slow Travel Speed Loaded (miles per hour)	1.3
Slow Travel Speed Unloaded (miles per hour)	1.5
Turing Radius (in.)	23-5/8
Controller Type	Curtis 1228
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1024>