

# Steel DC Powered Quick Lift 56 In. Raised Height 175 Lb. Capacity

**MODEL PEL-88S-D3**

Ergonomic Solutions / Powered Quick Lifts



## PRODUCT OVERVIEW

The DC powered quick lift is a quiet, lightweight unit used for transport and positioning loads quickly with just the push of the button. The unit is battery operated with a high density polyethylene platform. It features a low profile design for maneuvering in narrow aisles and confined spaces. The poly casters consist of two swivel and two swivel-locking that are standard. The DC system runs with an AC on-board charger.

## KEY FEATURES

- DC powered battery is fast and quiet
- White HDPE platform offers durability and aesthetics
- Chain driven platform operation provides precise positioning
- Touch-pad control allows for easy operation

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
172 lbs

**ASSEMBLED SIZE**  
23.5" W x 37.5625" L x 65.3125" H

**SHIP WEIGHT**  
225 lbs

**PACKAGE 1 SIZE**  
40" W x 48" D x 72" H

**COLOR / FINISH**  
Blue

**FREIGHT TYPE**  
LTL Palletized

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                  |                                  |
|----------------------------------|----------------------------------|
| Uniform Capacity (lb.)           | 175                              |
| Lowered Height (in.)             | 5-5/8                            |
| Raised Height (in.)              | 56                               |
| Caster Diameter (in.)            | 3                                |
| Caster Type                      | (2) Swivel (2) Swivel with Brake |
| Caster Material                  | Poly-on-Poly                     |
| DC Voltage                       | 24                               |
| AC Charger Voltage               | 115                              |
| Horizontal Load Center (in.)     | 9                                |
| Platform Width (in.)             | 23-1/2                           |
| Platform Length (in.)            | 18-1/2                           |
| Platform Thickness (in.)         | 1/2                              |
| Lift Speed (in./second) Loaded   | 17                               |
| Lift Speed (in./second) Unloaded | 10                               |
| Includes                         | Fully Welded Frame               |
| Handle Length (in.)              | 6                                |
| Handle Material                  | Steel                            |
| Battery Depth                    | 6                                |
| Battery Width                    | 8                                |
| Battery Height                   | 4                                |
| Battery Weight                   | 20                               |
| Battery Freight Class            | 60                               |
| Battery NMFC Number              | 60700                            |
| Battery NMFC Description         | Gel batteries on unit            |
| Lithium Battery Configuration    | C -- Contained In                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA