

Steel Quick Install Manual Trolley 13-5/8 In. x 20-3/16 In. x 20-3/8 In. 12000 Lb. Capacity Blue

MODEL QIT-12

Overhead Lifting / Quick Install Manual Trolleys



PRODUCT OVERVIEW

This quick install manual trolley is dependable, easy and safe to use. Designed to easily adjust to the width of virtually any S, H, W and M type I-beam. Width is adjusted with manual screw mechanism. Includes locking ring to prevent trolley width from changing accidentally. Manual screw mechanism may also be tightened to prevent trolley from moving (similar to a beam clamp). Each trolley includes four (4) rollers with sealed bearings for long life. A lifting eye is located at the bottom of the trolley for attaching a hoist (not included).

KEY FEATURES

- Manual adjusting screw with locking collar for quick and easy width adjustment
- Locking ring prevents trolley width from changing accidentally
- Sealed bearing rollers provide long life
- Lifting eye is located at the bottom of the trolley for safe hoist attachment

CORE PRODUCT DATA

ASSEMBLED WEIGHT
70 lbs

ASSEMBLED SIZE
20.1875" W x 13.625" L x 20.375" H

SHIP WEIGHT
70 lbs

PACKAGE 1 SIZE
14" W x 24" D x 13" H

COLOR / FINISH
Blue


FREIGHT TYPE
Parcel

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	12,000
Fits Beam Flange Width (in.)	4 to 11-3/4
Headroom (in.)	13 7/8
Min/Max Height (in)	17 1/4 to 20 3/8
Shackle Width (in)	4 1/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA