

Polyphenylene Sulfide Manual Rotary Drum Pump 10 In. 8 In. x 12 In. Black

MODEL RP-90RT

Drum Handling Equipment / Rotary Drum Pumps



PRODUCT OVERVIEW

The manual drum pump is designed for dispensing and transferring liquids out of fifty-five (55) gallon drum. It is ideal for transferring soluble, corrosive, volatile and aggressive chemicals. Suitable for use with acetone and ad-blue.

KEY FEATURES

- Designed for dispensing liquids out of fifty-five (55) gallon drum
- Outlet spout is made from 304 stainless steel
- Ideal for transferring soluble, corrosive, volatile and aggressive chemicals
- Suitable for use with acetone and ad-blue

CORE PRODUCT DATA

ASSEMBLED WEIGHT
5 lbs

ASSEMBLED SIZE
8" W x 10" L x 12" H

SHIP WEIGHT
6 lbs

PACKAGE 1 SIZE
7" W x 25" D x 7" H

COLOR / FINISH
Black


FREIGHT TYPE
Parcel

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Pump Type	Rotary - Vane
Flow Dispense Per Stroke (ml)	300
Maximum Fluid Temperature Degrees (Fahrenheit)	140 Degrees Fahrenheit / 60 Degrees Celsius
MNPT Bung Size (in.)	2
Suction Tube Length Maximum (in.)	42
Inlet Outside Diameter (in.)	1-1/4
Outlet Curved Spot Outside Diameter (in.)	1
Maximum Viscosity (SSU)	2000
Seal Construction	PTFE
Vane Construction	PTFE
Suction Tube Construction	PPS (Polyphenylene sulfide)
Adjustable Outlet Degrees	0 - 360
Application Liquids	acid, alkali, gasoline, diesel, machine oil, water, alcohol, thinner, Acetone, Ad-Blue, MEK and other chemical liquids
Component Materials	PPS, PTFE
Nitric Acid Resistance Percentage	40
Displacement per Stroke (ounces)	10.14
Pump Motor Type	Crank
Pump Mounting	Bung
Self-Priming	Yes

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=869>