

Steel Adjustable Powered Lift Stacker With Scale 62 In. Raised Height 2,000 Lb. Capacity Black / Yellow

MODEL S-62-AA-SCL

Ergonomic Solutions / Adjustable Powered Stacker w/ Scale



PRODUCT OVERVIEW

Want to transport and weigh items all in one load? Then an adjustable powered stacker, with a scale, is the perfect design for you! The high torque drive and lift motor handles heavy-duty jobs while moving through warehouse facilities easily and efficiently. The ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. The built-in safety circuit will automatically disable the entire unit if the emergency reverse belly switch is activated for more than five (5) seconds after which the unit must be re-set to return to normal operating conditions. This state-of-the-art safety device provides a high degree of operat...

KEY FEATURES

- Integral battery charger and a battery level gauge included
- Fingertip raise and lower buttons
- Safety belly reverse button improves worker safety
- Fully powered, digital scale readout

CORE PRODUCT DATA

ASSEMBLED WEIGHT
995 lbs

ASSEMBLED SIZE
58" W x 69" L x 82.6875" H

SHIP WEIGHT
1260 lbs

PACKAGE 1 SIZE
64" W x 74" D x 87" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,000
Service Range (in.)	2-1/8 to 62
Fork Width/Length (in.)	4 x 42
Adjustable Fork Spacing (in.)	8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	38-3/16 to 50 (ID)
Overall Mast Height (in.)	78
Drive Motor	DC 24V / 0.7 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 95 Ah
Battery Charger	DC 24V / 6 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Drive Wheel Qty./Diameter/Width (in.)	(1) 10 x 3-3/8
Front Wheel Qty./Diameter/Width (in.)	(2) 4 x 2.9
Stabilizer Wheel Qty./Diameter/Width (in.)	(2) 3 x 1.4
Steer Wheel Material	Poly-on-Steel
Load Wheel Material	Nylon
Travel Speed - Loaded (MPH)	3.1
Travel Speed - Unloaded (MPH)	3.8
Battery Depth	6.75
Battery Width	11.0625
Battery Height	9.25
Battery Weight	41
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point:

Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA