


# Plastic Speed Bump Glue Down Hardware 48 In. x 10 In. x 2 In. Yellow

**MODEL SBG-48**

Facilities Maintenance / Speed Bumps



## PRODUCT OVERVIEW

The speed bump is ideal for a variety of parking areas, both inside and out. The speed bump helps to control drivers from injuring people and property. The unit can be installed/removed by one person resulting in smooth portability. The strong recycled plastic construction can be used where traffic is frequent and can hold up to the constant day to day harm from chemicals and sunlight. Features a dual cable channel. The HD asphalt kit includes anchors, bolts and washers. The HD anchor should be epoxied (epoxy not included) into the ground and then the speed bump is secured to that anchor with a bolt and washer.

## KEY FEATURES

- 100% Recycled low density polyethylene (LDPE) offers long lasting rugged use
- Rugged construction resists marring by oil, road salt, sunlight and chemicals
- High-visibility yellow color draws attention and slows traffic
- Pre-drilled mounting holes make installation quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**18 lbs**

**ASSEMBLED SIZE**  
**10" W x 48" L x 2" H**

**SHIP WEIGHT**  
**19 lbs**

**PACKAGE 1 SIZE**  
**10" W x 48" D x 2" H**

**COLOR / FINISH**  
**Yellow**


**FREIGHT TYPE**  
**Parcel**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                            |           |
|--------------------------------------------|-----------|
| Compression Strength Per Square Inch (lb.) | 3200      |
| Number of Mounting Holes                   | 3         |
| Speed Bump Installation Type               | Glue-Down |
| Channel                                    | Yes       |
| Dual cable channel width (in.)             | 1         |
| Dual cable channel height (in.)            | 3/4       |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA