

Steel Tilt Master DC Powered Foot Control 12 Volt 4,000 Lb. Capacity Blue

MODEL TM-40-DC-FC

Ergonomic Solutions / Tilt Master & Tilt Master Straddle



PRODUCT OVERVIEW

The tilt master lifts and positions filled tote boxes or baskets without the need of a fork truck or lift table using the newly designed heavy-duty tilt master. The tilter will function as transporters by moving completed products from work station to work station without waiting for a fork truck. This lift has a thin profile to allow the user to get as close to the load as possible. It also has a standard floor lock and rolls easily on the phenolic steering wheels. Lift is designed to be used with open bottom pallets or skids. The unit is powered by a DC electric motor that includes an on-board battery charger, battery charge indicator gauge and foot control.

KEY FEATURES

- Folding ergonomic handle
- Two rigid and two swivel casters provide smooth and efficient mobility
- 90 Degrees tilt angle allows for better ergonomic access
- Foot pedal control for quick lifting and lowering

CORE PRODUCT DATA

ASSEMBLED WEIGHT
701 lbs

ASSEMBLED SIZE
41.0625" W x 75.5625" L x 28.3125" H

SHIP WEIGHT
699 lbs

PACKAGE 1 SIZE
40" W x 68" D x 29" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Fixed Fork Spacing (in.)	26
Operator Reach (in.)	7-1/4
Fork Width (in.)	6
Fork Length (in.)	38-1/8
Fully Rotated Fork Height (in.)	76-5/16
Lowered Height (in.)	3-5/8
Maximum Tilt Degree	90
Power	12V DC
Wheel Diameter (in.)	8
Wheel Width (in.)	3
Wheel Type	Phenolic
Folding Handle Length (in.)	20
Load Center (in.)	20
Fully Rotated Mast Height (in.)	33
Battery Depth	11
Battery Width	7
Battery Height	9
Battery Weight	42
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA